Tamiami Trail Flow Formula (TTFF) - Target Flow from WCA-3A to ENP

Daily Target Flow for	11/10/2026	to	11/16/2026	MAX	cfs

Observed Stage Data

Station	Variable	on	11/6/2026	Value	Unit
WCA-3A (Average for Site 63, 64 and 65)	Average Daily Stage			10.86	ft-NGVD29
NESRS2	Average Daily Stage			7.71	ft-NGVD29
Regulatory Stage WCA-3A	Average Daily Stage			10.50	ft-NGVD29

Observed Flow Data

Station	Variable	From	10/31/2026	to	11/6/2026	Value	Unit
S-12A	7-day Average Daily Flow					95	cfs
S-12B	7-day Average Daily Flow					51	cfs
S-12C	7-day Average Daily Flow					377	cfs
S-12D	7-day Average Daily Flow					708	cfs
S-333	7-day Average Daily Flow					598	cfs
S-333N	7-day Average Daily Flow					564	cfs
S-334	7-day Average Daily Flow					0	cfs
S-12s Total	7-day Average Daily Flow					1231	cfs
S333 + S333N - S334[1]	7-day Average Daily Flow					1163	cfs
Total Flow to ENP	7-day Average Daily Flow					2394	cfs

Meteorological Data

Forecasted	From	11/7/2026	to	11/13/2026	Value	Unit
WCA3 7-day Quantitative Precipitation Forecast (QPF)					0.59	in
3AS3WX - 7-day Total Forecasted PET					0.87	in

Observed	From	10/31/2026	to	11/6/2026	Value	Unit
WCA-3 7-day Total Observed NEXRAD Rainfall					3.58	in
3AS3WX 7-day Total Observed PET					0.87	in

TTFF Application

1	Previous week target flow (calculated with forecasted 7-day QPF and PET)	1392	cfs
2	Previous week target flow (recalculated with observed rainfall and PET)	1442	cfs
3	Adjustment for forecast (2-1)	50	cfs
4	This week calculated target flow	MAX	cfs
5	This week target flow with adjustment (3 + 4)	MAX	cfs
Average Daily Target Flow[2]		**MAX**	**cfs**

TTFF formula coefficients					
WCA-3A Average Stage (β1)	**NESRS2 Stage (β2)**	**Previous 7-day Average Flow (β3)**	**Forecast Precipitation (β4)**	**Forecast PET (β5)**	**Regulation Schedule Stage (β6)**
318.42	-44.62	0.644	24.32	-96.31	-221.79

Target flow is distributed from east to west (S-333, S-12D, S-12C, S-12B, and S-12A) to prioritize water deliveries to NESRS first and WSRS second, subject to downstream constraints.

[1]S-333 + S-333N - S-334 becomes zero if the sum of S-333 and S-333N is less than S-334 flow. Calculation is done daily.

[2]Actual discharges may vary from target discharges because of changing hydrologic conditions.

